

# MATERIAL SAFETY DATA SHEET

PAR-WAY TRYSON COMPANY  
107 BOLTE LANE PH: (636) 629-4545  
ST. CLAIR, MO 63077 FAX: (636) 629-1330  
(8:30-5:00 P.M. CST)

**SECTION 1 PRODUCT IDENTIFICATION**  
**PRODUCT NAME:** PURICIT ODOR ELIMINATOR  
**PRODUCT CLASS:** AEROSOL CITRUS DEODORIZER  
**DATE PREPARED:** 06/09  
**ITEM #:** 06700

<u>HIMS RATING</u>	
HEALTH	2
FLAMMABILITY	2
REACTIVITY	1
P.P. EQUIPMENT	X

## SECTION 2 HAZARDOUS INGREDIENTS

INGREDIENT	CAS#	ACGIH	OSHA	OTHER	% OPTIONAL
CITRUS TERPENES (CITRUS OIL)			N/A		
DIFLOUROETHANE BLEND	5989-27-5	1000 PPM			20%

THIS MSDS WAS PREPARED USING THE GUIDELINES SET BY 49 CFR 1910.1200 AND SARA III

## SECTION 3 PHYSICAL DATA

BOILING POINT: N/A PERCENT VOLATILE: 97.7%  
VAPOR PRESSURE: 60 PSI @ 70° F VOC (GRAM/LITRE): N/A  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
SPECIFIC GRAVITY: 0.912 SOLUBILITY IN WATER: EMULSIFIABLE  
VISCOSITY: 11 CPS APPEARANCE: MILKY WHITE EMULSION  
ODOR: CITRUS

## SECTION 4 FIRE AND EXPLOSION DATA

FLASH POINT: -58°F PROPELLANT 128°F CONCENTRATE  
EXPLOSIVE LIMITS LOWER: 1.8 % UPPER: 9.5 %  
EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, HALON  
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, NITROGEN  
FIRE FIGHTING PROCEDURES AND EXPLOSION HAZARDS:  
WEAR SELF CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN A POSITIVE PRESSURE MODE. WATER FOG MAY BE USED TO HELP COOL CONTAINERS TO HELP MINIMIZE PRESSURE BUILD-UP. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND TO SOURCES OF IGNITION. REPORTS HAVE BEEN MADE OF IGNITION FROM PILOT LIGHTS, HEATERS, ETC AFTER VAPORS HAVE BEEN MOVED BY VENTILATING FANS. EXPLODING CANS MAY TRAVEL GREAT DISTANCES SPEWING BURNING MATERIALS. EXPOSURE TO TEMPERATURES OVER 120°F MAY CAUSE CANS TO BURST.

## SECTION 5 REACTIVITY DATA

STABILITY: NORMALLY STABLE  
INCOMPATIBILITY: STRONG OXIDIZERS, HEAT AND IGNITION SOURCES  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
CONDITION TO AVOID: DO NOT STORE ABOVE 120° F. DO NOT STORE IN DIRECT SUNLIGHT

## SECTION 6 HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVELS: 1000 PPM PROPELLANT

### ACUTE EFFECTS

**EYES:** SLIGHT TRANSIENT IRRITATION, REDNESS, PAIN  
**SKIN:** POSSIBLE IRRITATION TO SENSITIVE SKIN  
**BREATHING:** POSSIBLE IRRITATION TO THE RESPIRATORY SYSTEMS OF SENSITIVE INDIVIDUALS

**CHRONIC EFFECTS**

TARGET ORGAN/SYSTEMATIC EFFECTS:

POSSIBLE RESPIRATORY AND OR CENTRAL NERVOUS SYSTEM DAMAGE WITH GROSS OVER EXPOSURE OVER A LONG PERIOD OF TIME

**FIRST AID**

**EYES:** IRRIGATE WITH FLOWING WATER AT LEAST 10 MINUTES. HOLD LIDS OPEN AS IT HELPS PREVENT SCRATCHING AND MINIMIZE IRRITATION. SEEK MEDICAL ATTENTION AS MATERIAL MAY BECOME IMBEDDED.

**SKIN:** WASH WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

**INGESTION:** DO NOT INDUCE VOMITING. CALL A PHYSICIAN AND OR POISON CONTROL CENTER IMMEDIATELY.

**INHALATION:** REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT GIVE OXYGEN. CALL A PHYSICIAN AS EXCESSIVE EXPOSURE MAY CAUSE IRRITATION TO THE UPPER RESPIRATORY SYSTEM.

---

**SECTION 7 PRECAUTIONS FOR STORAGE AND DISPOSAL**

**STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:**

CLEAN WITH SOAP AND WATER, VENTILATE, EXCESSIVE CONCENTRATION OF VAPORS ARE FLAMMABLE. WASTE DISPOSAL METHODS: DO NOT PUNCTURE OR INCINERATE "EMPTY" OR FULL CANS. ONCE SPILLS OR LEAKS ARE CLEANED UP, DISPOSE OF WASTE IN ACCORDANCE WITH GOVERNMENTAL ORDINANCES.

---

**SECTION 8 HANDLING PRECAUTIONS**

**VENTILATION:** GENERAL VENTILATION SHOULD BE ADEQUATE FOR NORMAL USE. IF USING IN CONFINED AREAS USE NECESSARY MEANS OF VENTILATION TO KEEP FROM EXCEEDING THE TLV.

**RESPIRATORY:** IF USING IN AREAS WHERE THE TLV IS LIKELY TO BE EXCEEDED USE A NIOSH/MSA APPROVED RESPIRATOR.

**SKIN:** USE CHEMICAL RESISTANT GLOVES IF THE POSSIBILITY OF PROLONGED CONTACT EXISTS.

**STORAGE:** STORE BELOW 120° F. AVOID DIRECT SOURCES OF HEAT AND IGNITION. DO NOT USE DEFORMED OR DAMAGED CANS. KEEP OUT OF THE REACH OF CHILDREN. CONSULT LOCAL FIRE MARSHALL AND INSURANCE REPRESENTATIVES FOR SPECIFIC STORAGE REQUIREMENTS IN YOUR AREA.

---

**SECTION 9 TRANSPORTATION AND REGULATORY INFORMATION**

**A. GROUND**

PROPER SHIPPING NAME: CONSUMER COMMODITY

CONTAINER SIZE: 6- 6 OZ. NET WT PER CASE

DOT CLASSIFICATION: ORM-D

DOT MARKINGS: ORM-D

DOT HAZARD CLASS: N/A

PROPELLANT: PROPANE/ISOBUTANE

SARA III REPORTABLE QUANTITY: 1,000 LBS.

NFPA 30B WAREHOUSE CLASSIFICATION: LEVEL 1

**B. AIR**

PROPER SHIPPING NAME: CONSUMER COMMODITY

DOT CLASSIFICATION: ORM-D-AIR

DOT LABELING/MARKINGS: ID8000/ORM-D-AIR

DOT HAZARD CLASS: 9.0

PROPELLANT: PROPANE/ISOBUTANE

SARA III REPORTABLE QUANTITY: 25,000 LBS

NFPA 30B WAREHOUSE CLASSIFICATION: LEVEL 1

**SECTION 9 TRANSPORTATION AND REGULATORY INFORMATION (CON'T)**

**C. IMDG**

PROPER SHIPPING NAME: AEROSOL, FLAMMABLE  
DOT CLASSIFICATION: FLAMMABLE LIQUID UN-1950  
DOT MARKINGS: ORM-D  
LOT PLACARD: LIMITED QUANTITY  
DOT HAZARD CLASS: 2.0  
PROPELLANT: PROPANE/ISOBUTANE  
SARA III REPORTABLE QUANTITY: 25,000 LBS  
NFPA 30B WAREHOUSE CLASSIFICATION: LEVEL 1

---

**DISCLAIMER:**

THE FOREGOING INFORMATION HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF THE NEED THAT THE DATA IS CORRECT, APPLICABLE AND SUITABLE TO THEIR CIRCUMSTANCES. STANDARDS CHANGE WITHOUT NOTICE; IT IS THE RESPONSIBILITY OF THE RECIPIENT TO ASSURE THAT THEIR PERSONNEL HAVE BEEN NOTIFIED OF ANY CHANGES WHICH MAY AFFECT THEM. THE DATA PROVIDED ON THE MSDS ARE NOT MEANT TO BE USED AS SPECIFICATIONS, ONLY GUIDELINE INFORMATION AS TO SAFE USE OF THE PRODUCT. USER SHOULD ALSO REFER TO OSHA, STATE AND LOCAL SAFETY LAWS BEFORE USE.  
PREPARED BY: ROBERT M. SMITH, TECHNICAL DIRECTOR

